



An **RPM** Company

FOR IMMEDIATE RELEASE
23 July 2009

CONTACT: Barbara Catlow
401-822-4100
Phil Loscoe
401-521-2700

**DRYVIT'S NEW MOJAVE E™ FINISH WEIGHS 40% LESS,
IS EASIER TO APPLY & OFFERS SUPERIOR CRACK RESISTANCE
THAN STANDARD ELASTOMERIC FINISHES**

(West Warwick, RI) – Mojave E, a new premixed, lightweight finish that provides better performance characteristics than standard elastomeric finishes over stucco, is now available from Dryvit Systems, Inc.

Mojave E is a 100% acrylic-based coating that contains 20% post-consumer recycled glass to offer improved flexibility, ease of application and superior crack resistance. The patented formulation of Mojave E creates a finish that offers the same volume and coverage area as the standard five gallon bucket of Dryvit finish, but actually weighs 40% less than the standard pail. It also offers superior workability and, because it is lighter, it reduces applicator arm fatigue during installation.

The improved flexibility enhances crack-bridging on walls, meaning fewer callbacks and lower bottom-line cost. In addition, its lighter weight also reduces transportation costs. Because of its unique characteristics, the E Finish product line earned a United States Patent for its unique formulation and lightweight properties.

“Mojave E is a superior, value-added alternative to traditional elastomeric finishes that is basically a win, win for everyone,” said Tony Stall, Vice President of Marketing and Sustainability at Dryvit Systems, Inc.

-MORE-

“Because it is 40% lighter, applicators find it easier to carry and apply. It is also easier on the environment because it is made from recycled material, and it will save on fuel and transportation costs as well.

Last but not least, when used as part of an Outsulation® system, it possesses the same Dryvit quality, performance and energy efficiency that building owners, applicators, engineers and architects alike have come to rely upon.”

Available in standard and custom colors, the durable Mojave E provides surface color and texture for Dryvit systems. It can be applied over other properly prepared substrates such as exterior masonry, stucco, precast or cast-in-place concrete. It is also suitable for interior applications. It can be trowel applied or spray applied with a hopper gun or pole gun-type sprayer. Mojave E is shipped in 18 kg (40 lb) pails and yields an approximate coverage of 120 sq. ft. /pail. Used in combination with other Dryvit products with recycled content, it produces the most environmental, energy-saving wall cladding in the industry.

About Dryvit Systems, Inc.

Dryvit Systems, Inc. (www.dryvitisgreen.com, www.dryvit.com) is the leading North American manufacturer of Exterior Insulation and Finish Systems (EIFS), a highly energy efficient cladding technology the company brought to the US from Europe in 1969. A Fortune 1,000 company, Dryvit operates all North American manufacturing facilities to both ISO 9001:2008 and 14001:2004 standards. Dryvit is a member of and is actively engaged in many relevant construction related organizations such as AWCI, EIMA, NAHB, USGBC, AIA, and CSI, and works both independently and within those organizations to promote energy efficient construction methods that create jobs, reduce reliance on non renewable energy sources, and reduce the carbon footprint of our nation’s buildings.

A subsidiary of the more than \$3 billion industrial sealants and coatings brand holder RPM, Inc. of Medina, Ohio (NYSE:RPM), Dryvit is headquartered in West Warwick, Rhode Island and operates manufacturing facilities in Georgia, Oklahoma, California, Canada, Poland and China.